

Rapid one-component semigloss UV varnish system (all wood types)

Epifanes Rapidclear (amber transparent) and Epifanes Rapidcoat (light teaktone) are two semi gloss finishes. Provide an enhancing UV protecting film with perfect bonding to teak and other oily wood, prevent discoloring and emphasize the natural wood grain. Excellent water resistance, maximum durability, UV protection and longevity. Quick recoatability without sanding.

Full UV resistant semi-gloss system on all interior and exterior woodwork above the waterline. Also as quick drying grain filling coat prior to applying Epifanes Clear Gloss Varnish or Epifanes Woodfinish Gloss. Maintenance of one-and twocomponent varnishes regardless which brand. In the latter case, sand the last coat Rapidclear with P220

Product: Epifanes Rapidclear and/or Epifanes Rapidcoat with UV filter



Rapid one-component semigloss UV varnish system

After surface preparation:	Step 1
Product	EPIFANES Rapidclear / Rapidcoat
Number of coats	5 - 6
Thinner	EPIFANES Brushthinner for Paint & Varnish
Percentage	0-5%
Drying time @ 18° C	5 hours
Abrasive paper	Sanding between coats is not necessary. For a smoother surface however, lightly sand by hand with P280-320 dry
Remarks	Use Epifanes Rapidcoat for camouflaging wood colour differences. By applying more coats Rapidcoat, the wood will appear darker.

For a high gloss finish, sand final coat Rapidclear with P220 dry and apply two or more coat Epifanes Clear Gloss Varnish or Epifanes Woodfinish Gloss.

For a satin interior finish, sand the final coat Rapidclear with P220 and apply one or two coats Epifanes Rubbed Effect Varnish.