

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes PU Speedcoat Comp. B (cure)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category
 - PROC11 Non industrial spraying
 - PROC7 Industrial spraying
 - PROC10 Roller application or brushing
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category
 - AC11 Wood articles
 - AC7 Metal articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 1)

Acute Tox. 4	H332	Harmful if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· Additional information: For professional use only.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Hexamethylene-1,6 diisocyanate homopolymer
heptan-2-one

n-butyl acetate

hexamethylene-di-isocyanate

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Contains isocyanates. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 2)

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17	Hexamethylene-1,6 diisocyanate homopolymer ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	10-25%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics. (Note-P) ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H336	2.5-10%
CAS: 110-43-0 EINECS: 203-767-1 Index number: 606-024-00-3 Reg.nr.: 01-2119902391-49	heptan-2-one ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H336	2.5-10%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37	hexamethylene-di-isocyanate ⚠ Acute Tox. 3, H331 ⚠ Resp. Sens. 1, H334 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 EUH204 Specific concentration limits: Resp.Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.1-<0.5%

- Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 3)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

* **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

* **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 4)

- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
110-43-0 heptan-2-one	
WEL	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk
822-06-0 hexamethylene-di-isocyanate	
WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
110-43-0 heptan-2-one	
WEL	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk
822-06-0 hexamethylene-di-isocyanate	
WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 5)

· Regulatory information WEL: EH40/2020

· DNEL (Derived No Effect Level) voor professionals

28182-81-2 Hexamethylene-1,6 diisocyanate homopolymer

Inhalative	Acute / short term - local defects	0.07 mg/m ³ (Employees)
	Long-term - local effects.	0.035 mg/m ³ (Employees)

123-86-4 n-butyl acetate

Dermal	Short-term - systemic effects.	11 mg/kg (Employees)
	Long-term - systemic effects.	11 mg/kg/day (Employees)
Inhalative	Long-term - local effects.	300 mg/m ³ (Employees)
	Short-term systemic effects.	600 mg/m ³ (Employees)
	Short term - local effects.	600 mg/m ³ (Employees)
	Long-term - systemic effects.	300 mg/m ³ (Employees)

64742-95-6 Hydrocarbons, C9, aromatics. (Note-P)

Oral	Long-term - systemic effects.	11 mg/kg/day (General population)
Dermal	Long-term - systemic effects.	25 mg/kg/day (Industry)
	Long-term systemic effects.	11 mg//kg/day (General population)
Inhalative	Long-term - systemic effects.	32 mg/m ³ (General population)
	Long-term - systemic effects.	150 mg/m ³ (Industry)
	Long-term exposure (8 hours TWA) 19 ppm	100 mg/m ³ (Occupational exposure limits)

110-43-0 heptan-2-one

Oral	Long-term - systemic effects.	23.32 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	84.31 mg/m ³ (General population)

822-06-0 hexamethylene-di-isocyanate

Inhalative	Acute / short term - local defects	0.07 mg/m ³ (Employees)
	Long-term - local effects.	0.035 mg/m ³ (Employees)

· DNEL (Derived No Effect Level) for general audience

123-86-4 n-butyl acetate

Oral	Long-term systemic effects.	2 mg/kg bw/day (General population)
	Short-term - systemic effects.	6 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	6 mg/kg bw/day (General population)
	Long-term - local effects.	35.7 mg/m ³ (General population)
Inhalative	Short-term - systemic effects.	6 mg/kg (General population)
	Long-term - systemic effects.	35.7 mg/m ³ (General population)
	Short-term - systemic effects.	300 mg/kg (General population)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 6)

	Short-term - local effects.	300 mg/m ³ (General population)
110-43-0 heptan-2-one		
Dermal	Long-term - systemic effects.	54.27 mg/kg bw/day (Employees)
Inhalative	Acute - systemic effects.	1,516 mg/m ³ (Employees)
	Long-term - systemic effects.	394.25 mg/m ³ (Employees)
	Long term - systemic effects.	23.32 mg/kg bw/day (General population)

PNECs

28182-81-2 Hexamethylene-1,6 diisocyanate homopolymer

Aquatic compartment.	0.049 mg/l (Freshwater)
Aquatic compartment.	0.005 mg/l (Seawater)
STP	8.42 mg/l (Segmentation, Targeting and Positioning)
Soil	0.674 mg/kg (Freshwater)
Soil	0.523 mg/kg (soil)
Sediment	0.067 mg/kg (Seawater)

123-86-4 n-butyl acetate

Aquatic compartment.	0.18 mg/l (Freshwater)
Aquatic compartment.	0.018 mg/l (Seawater)
STP	35.6 mg/l (Segmentation, Targeting and Positioning)
Soil	0.981 mg/kg (Freshwater)
Intermittent	0.36 mg/l (Intermittent)
Soil	0.0903 mg/kg (soil)
Sediment	0.0981 mg/kg (Seawater)

110-43-0 heptan-2-one

Fresh water sedimentation	1.89 mg/kg (Freshwater)
Sea water sedimentation	0.189 mg/kg (Seawater)
Aquatic compartment.	0.0982 mg/l (Freshwater)
	0.982 mg/l (Intermittent)
Aquatic compartment.	0.00982 mg/l (Seawater)
STP	12.5 mg/l (Segmentation, Targeting and Positioning)
Soil	0.321 mg/kg (soil)

822-06-0 hexamethylene-di-isocyanate

Aquatic compartment.	0.049 mg/l (Freshwater)
Aquatic compartment.	0.005 mg/l (Seawater)
STP	8.42 mg/l (Segmentation, Targeting and Positioning)
Soil	0.674 mg/kg (Seawater)
Soil	0.523 mg/kg (soil)
Sediment	0.067 mg/kg (Seawater)

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 7)

· Ingredients with biological limit values:

822-06-0 hexamethylene-di-isocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period of exposure

Parameter: isocyanate-derived diamine

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see item 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX

In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 8)

- Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties
 - General Information
 - Physical state Fluid
 - Colour: According to product specification
 - Odour: Characteristic
 - Odour threshold: Not determined.
 - Melting point/freezing point: Undetermined.
 - Boiling point or initial boiling point and boiling range 36 °C (64742-95-6 Hydrocarbons, C9, aromatics. (Note-P))
 - Flammability Not applicable.
 - Lower and upper explosion limit
 - Lower: 1.2 Vol % (123-86-4 n-butyl acetate)
 - Upper: 7.5 Vol % (123-86-4 n-butyl acetate)
 - Flash point: 27 °C
 - Auto-ignition temperature: Product is not selfigniting.
 - Decomposition temperature: Not determined.
 - pH Not determined.
 - Viscosity:
 - Kinematic viscosity at 20 °C 50 s (ISO 4 mm)
 - Dynamic: Not determined.
 - Solubility
 - water: Fully miscible.
 - Partition coefficient n-octanol/water (log value) Not determined.
 - Vapour pressure at 20 °C: 10.7 hPa (123-86-4 n-butyl acetate)
 - Density and/or relative density
 - Density at 20 °C: 1.04116 g/cm³
 - Relative density Not determined.
 - Vapour density Not determined.

- 9.2 Other information
 - Appearance:
 - Form: Fluid
 - Important information on protection of health and environment, and on safety.
 - Ignition temperature: 370 °C
 - Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 9)

- Solvent content:
- Organic solvents: 35.0 %
- VOC content: 34.98 %
- VOC content:
364.2 g/l / 3.04 lb/gal
- Solids content: 64.7 %
- Change in condition
- Evaporation rate Not determined.

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg bw (rat)
------	------	-----------------------

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 10)

Dermal	LD50	>5,000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)
110-43-0 heptan-2-one		
Oral	LD50	1,670 mg/kg bw (rat)
Dermal	LD50	12,600 mg/kg bw (rabbit)
	Short-term exposure (15 minutes): 100 ppm	475 mg/m ³ (Occupational exposure limits)
822-06-0 hexamethylene-di-isocyanate		
Oral	LD50	738 mg/kg bw (rat)
Dermal	LD50	593 mg/kg bw (rat)

- Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure
May cause respiratory irritation. May cause drowsiness or dizziness.
- 11.2 Information on other hazards

• Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 11)

- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR, IMDG, IATA UN1263

- 14.2 UN proper shipping name
- ADR 1263 PAINT
- IMDG, IATA PAINT

- 14.3 Transport hazard class(es)

- ADR



- Class 3 (F1) Flammable liquids.
- Label 3

- IMDG, IATA



- Class 3 Flammable liquids.
- Label 3

- 14.4 Packing group

- ADR, IMDG, IATA III

- 14.5 Environmental hazards: Not applicable.

- 14.6 Special precautions for user Warning: Flammable liquids.

- Hazard identification number (Kemler code): 30

- EMS Number: F-E, S-E

- Stowage Category A

- 14.7 Maritime transport in bulk

according to IMO instruments Not applicable.

- Transport/Additional information:

- ADR

- Limited quantities (LQ) 5L

- Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging:
30 ml

Maximum net quantity per outer packaging:
1000 ml

- Transport category 3

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 12)

· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- National regulations:
- Technical instructions (air):

Class	Share in %
I	≤0.5
NK	25-50
- Waterhazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H332 Harmful if inhaled.

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 12 (replaces version 11)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. B (cure)

(Contd. of page 13)

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

- Department issuing SDS: Research & Development.
- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl
- Abbreviations and acronyms:
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 3: Flammable liquids - Category 3
 - Acute Tox. 3: Acute toxicity - Category 3
 - Acute Tox. 4: Acute toxicity - Category 4
 - Skin Irrit. 2: Skin corrosion/irritation - Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
 - Resp. Sens. 1: Respiratory sensitisation - Category 1
 - Skin Sens. 1: Skin sensitisation - Category 1
 - STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
 - Asp. Tox. 1: Aspiration hazard - Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
- * Data compared to the previous version altered.