

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Epoxy HB Coat Comp. A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU21 Consumer uses: Private households / general public / consumers
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category AC7 Metal articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
base component of a high building epoxybased coating
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
Oosteinderweg 32
1432 AL Aalsmeer
Netherlands
tel.+31 297-360366
email: info@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number: +61 7 5563 1222 (Monday-Friday 8:30am-5:00pm)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



corrosion

Eye Dam. 1

H318 Causes serious eye damage.



environment

Aquatic Chronic 2

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 1)



Skin Irrit. 2

H315 Causes skin irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS05



GHS07



GHS09

- Signal word Danger
- Hazard-determining components of labelling:
bis[4-(2,3-epoxypropoxy)phenyl]propane
Butan-1-ol
Fatty acids, C18-unsaturated dimers, polymers with bisphenol A and epichlorohydrin
- Hazard statements
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2	bis[4-(2,3-epoxypropoxy)phenyl]propane ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit.2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	10-25%
CAS: 67989-52-0	Fatty acids, C18-unsaturated dimers, polymers with bisphenolA and epichlorohydrin ⚠ Skin Sens. 1, H317	10-25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥2.5-<10%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	2.5-10%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	Butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥3-<10%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	Zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≥0.25-≤1%
CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10	propylidynetrimethanol ⚠ Repr. 2, H361fd	<0.3%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 3)

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact:
Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 4)

- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Not required.
Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

71-36-3 Butan-1-ol

WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk
-----	--

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

71-36-3 Butan-1-ol

WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk
-----	--

- Regulatory information WEL: EH40/2020

- DNEL (Derived No Effect Level) voor professionals

1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane

Dermal	Long-term - systemic effects.	0.75 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	4.93 mg/m ³ (Employees)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 5)

1330-20-7 Xylene		
Dermal	Long-term systemic effects.	212 mg//kg/day (Employees)
Inhalative	Acute / short term - local defects	442 mg/m ³ (Employees)
	Long-term - local effects.	221 mg/m ³ (Employees)
	Long-term - systemic effects.	221 mg/m ³ (Employees)
7779-90-0 trizinc bis(orthophosphate)		
Dermal	Long-term - systemic effects.	8.3 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	1 mg/m ³ (Employees)
71-36-3 Butan-1-ol		
Inhalative	Long-term - local effects.	310 mg/m ³ (Employees)
1314-13-2 Zinc oxide		
Dermal	Long-term - systemic effects.	83 mg/kg/day (Employees)
Inhalative	Long-term - local effects.	0.5 mg/m ³ (Employees)
	Long-term - systemic effects.	5 mg/m ³ (Employees)
77-99-6 propylidynetrimethanol		
Oral	Long-term - systemic effects.	0.34 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	0.58 mg/m ³ (General population)
· DNEL (Derived No Effect Level) for general audience		
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Oral	Long-term systemic effects.	0.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	0.089 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	0.87 mg/m ³ (General population)
1330-20-7 Xylene		
Oral	Long-term systemic effects.	12.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	125 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	65.3 mg/m ³ (General population)
	Long-term - local effects.	65.3 mg/m ³ (General population)
	Acute / short-term - systemic effects.	260 mg/m ³ (General population)
	Acute / short-term - local effects.	260 mg/m ³ (General population)
7779-90-0 trizinc bis(orthophosphate)		
Oral	Long-term systemic effects.	0.83 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	8.3 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	1.25 mg/m ³ (General population)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 6)

71-36-3 Butan-1-ol		
Oral	Long-term systemic effects.	mg/kg bw/day (rat)
Dermal	Long-term - systemic effects.	3.125 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	55.357 mg/m ³ (General population)
	Long-term - local effects.	155 mg/m ³ (General population)
1314-13-2 Zinc oxide		
Oral	Short-term - systemic effects.	0.83 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	83 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	2.5 mg/m ³ (General population)
77-99-6 propylidynetrimethanol		
Dermal	Long-term - systemic effects.	0.94 mg/kg bw/day (Employees)
	Acute / short-term - local effects.	0.34 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	3.3 mg/m ³ (Employees)
PNECs		
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane		
Freshwater	0.006 mg/l (Freshwater)	
Marine water	0.001 mg/l (Marine water)	
Sediment (freshwater)	0.341 mg/kg sed dw (Freshwater sediment)	
Sediment (marine water)	0.034 mg/kg sed dw (5)	
STP	10 mg/l (Segmentation, Targeting and Positioning)	
Soil	0.065 mg/kg (soil)	
1330-20-7 Xylene		
Freshwater	0.327 mg/l (Freshwater)	
Marine water	0.327 mg/l (Marine water)	
Sediment (freshwater)	12.46 mg/kg sed dw (Freshwater)	
Sediment (marine water)	12.46 mg/kg sed dw (Marine water)	
STP	6.58 mg/l (Segmentation, Targeting and Positioning)	
Soil	2.31 mg/kg (soil)	
7779-90-0 trizinc bis(orthophosphate)		
Marine water	6.1 µg/L (Marine water)	
Freshwater	20.6 µg/l (Freshwater)	
Sediment (freshwater)	117.8 mg/kg sed dw (Freshwater)	
Sediment (marine water)	56.5 mg/kg sed dw (Marine water)	
STP	0.1 mg/l (Segmentation, Targeting and Positioning)	
Soil	35.6 mg/kg (soil)	
71-36-3 Butan-1-ol		
Freshwater	0.082 mg/l (Freshwater)	

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 7)

Marine water	0.008 mg/l (Marine water)
Sediment (freshwater)	0.324 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.032 mg/kg sed dw (Marine water)
STP	2,476 mg/l (Segmentation, Targeting and Positioning)
Soil	0.017 mg/kg (soil)

1314-13-2 Zinc oxide

Marine water	6.1 µg/L (Marine water)
Freshwater	20.6 µg/l (Freshwater)
Sediment (freshwater)	117.8 mg/kg sed dw (Freshwater)
Sediment (marine water)	56.5 mg/kg sed dw (Marine water)
STP	0.1 mg/l (Segmentation, Targeting and Positioning)
Soil	35.6 mg/kg (soil)

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

· Respiratory protection:

Filter AX

In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 9)

- 9.2 Other information
- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Auto-ignition temperature: Product is not selfigniting.
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- Solvent content:
- Organic solvents: 13.3 %
- VOC content: 13.29 %
VOC content:
239.2 g/l / 2.00 lb/gal

- Solids content: 86.7 %
- Change in condition
- Evaporation rate Not determined.

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 10)

- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity
Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

1330-20-7 Xylene

Dermal	Short-term exposure (15 minutes): 100 ppm	442 mg/m ³ (Occupational exposure limits)
	Long-term exposure (8 hours TWA): 50 ppm	221 mg/m ³ (Occupational exposure limits)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5,000 mg/kg bw (rat)
Inhalative	LC50/4 h	5.7 mg/l (rat)

71-36-3 Butan-1-ol

Oral	LD50	790 mg/kg bw (rat)
Dermal	LD50	3,400 mg/kg bw (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

1314-13-2 Zinc oxide

Oral	LD50	7,950 mg/kg bw (mouse)
	LD50	>15,000 mg/kg (rat)

77-99-6 propylidynetrimethanol

Oral	LD50	14,100 mg/kg bw (rat)
------	------	-----------------------

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

7779-90-0 trizinc bis(orthophosphate)

ErC50	>100 mg/l (desmodesdus subspicatus)
LC50 (96 hours)	>1,000 mg/l ((Regenboogforel))
EC50 (48 hours)	>1,000 mg/l (daphnia magna)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 11)

- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Toxic for fish
- Additional ecological information:
- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
- ADR 1263 PAINT, ENVIRONMENTALLY HAZARDOUS
- IMDG PAINT, MARINE POLLUTANT
- IATA PAINT

- 14.3 Transport hazard class(es)

- ADR



- Class 3 (F1) Flammable liquids.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31




Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 12)

· Label	3
· IMDG	
 	
· Class	3 Flammable liquids.
· Label	3
· IATA	
	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	No Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 13)

- | | |
|----------------------------|--|
| · Excepted quantities (EQ) | Code: E1
Maximum net quantity per inner packaging:
30 ml
Maximum net quantity per outer packaging:
1000 ml |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III, ENVIRONMENTALLY
HAZARDOUS |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
500 t
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	10-25
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 15 (replaces version 14)

Revision: 07.12.2022

Trade name: Epifanes Epoxy HB Coat Comp. A

(Contd. of page 14)

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.

- Department issuing SDS: Research & Development.
- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (UK REACH)
 - PNEC: Predicted No-Effect Concentration (UK REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 3: Flammable liquids - Category 3
 - Acute Tox. 4: Acute toxicity - Category 4
 - Skin Irrit. 2: Skin corrosion/irritation - Category 2
 - Eye Dam. 1: Serious eye damage/eye irritation - Category 1
 - Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
 - Skin Sens. 1: Skin sensitisation - Category 1
 - Repr. 2: Reproductive toxicity - Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
 - STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2
 - Asp. Tox. 1: Aspiration hazard - Category 1
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
 - Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
- * Data compared to the previous version altered.